

COPPUS Air MAX-12

Economical, high-volume tube axial blower

MODEL/SPECIFICATIONS

MOTOR

TE 3/4 HP with integral on/off switch, 115V/6.8 amp, Class B insulation, auto reset thermal overload protection; GFCI at plug end on 115V models.

FREE AIR

2,200 cfm (3,740 m³/hr)

WEIGHT

44 lbs (18.14 kg)

HOUSING

18-gauge steel, powder-coated with carry handle and anti-vibration foot pads; rolled bead on ends for added strength and attaching flexible ducting; safety screens attached per OSHA guidelines.

PLEASE NOTE:

Not available for Class 1, Div. 1 (hazardous locations) applications.


DESCRIPTION

This 12 in (305 mm), lightweight, rugged blower delivers up to $2,200 \text{ cfm } (3,740 \text{ m}^3/\text{hr})$ for confined space ventilation and fresh air supply.

FEATURES / ADVANTAGES

- · Rugged, all-steel housing construction
- · Integral on/off motor switch
- Fixed guide vanes for improved performance
- Glass-reinforced, polypropylene, non-sparking fan blade
- 20 ft (6.1 m) cord with GFCl at plug end
- · Anti-vibration foot pads
- · Available with TE motors only; not for use in hazardous areas





TECHNICAL DATA

FREE AIR DECIBEL LEVELS						
Air MAX 12	74 dBA					

AIR FLOW THROUGH DUCT (STRAIGHT RUNS)									
MODEL	FREE AIR		10 ft 3.05 m		20 ft 6.10 m		30 ft 9.15 m		
	cfm	m³/hr	cfm	m³/hr	cfm	m³/hr	cfm	m³/hr	
Air MAX	2,200	3,740	2,120	3,602	2,025	3,440	1,890	3,211	





Mountain Controls









Portable Ventilators
Fans & Blowers
Welding Fume Exhausters
Ducts







POWERS
PROCESS CONTROLS
Quality...Our Commitment

Control Valves – Globe Type Temperature Regulators Self-Contained Temperature Controllers







MARSH

Pressure Gauges Thermometers Needle Valves and Diaphragm Seals







Precision Air Regulators Air, Gas, Steam & Water Regulators Vacuum and Backpressure Regulators I/P and E/P Transducers





Electric Actuators Modulating Controllers Spring Return – SURE Mounting to your valves.






Electric Actuators
Spring Return Electric Actuators











Process Controllers
Multi-Loop Process Indicators with Switches







Ball Valves – 3-piece Pneumatic Actuators Electric Actuators Specialty Valves







Custom Actuator Solutions Electric actuators mounted and tested to the valve of your choice. Custom lightweight actuators for compact solutions



Salt Lake City, UT 84109 Phone: 801-487-8795 Seattle, WA 98125 Phone: 206-316-2330

www.mountaincontrols.com

info@mountaincontrols.com