T2 & T2E Series Specs



Combination of weatherproof construction and phenolic case makes the T-2 and T-2E series thermometers ideal for outdoor service. These thermometers are also highly suited to installation where vibration typically causes stability problems. Each unit features a red marking pointer to indicate the highest temperature reached between readings.

SPECIFICATIONS

INDICATOR ACCURACY: +2% of span over entire scale.

Ranges:

30-250° F

50-350° F

0-120° C

0-150° C

20-180° C

DIAL SIZE: 3 7/8" diameter.

BOURDON TUBE: High torque spiral design; phospor bronze material.

CASE & RING: Fabricated Polypropart case. Brass ring, painted black, with special gasketing between the ring and case to ensure a water-proof construction.

DAIL: Aluminum; black background with white letters and scale.

POINTER: Aluminum; painted white.

CASE STYLES: Direct mount cases available with a ½ NPT union connection located at center back, lower back, or case bottom. Remote mount cases are equiped with a bracket for wall or panel mounting, with the capillary outlet at 30° from horizontal.

DIRECT MOUNT:

LB = Lower Back Connection

CB = Center Back Connection

BM = Bottom Mount Connection

CAPILLARY: Remote mount units are supplied as standard with 10' of double braided capillary.

RECALIBRATION: An external adjusting screw, located on the back of the case, allows readjustment of the pointer setting.

MAXIMUM TEMPERATURE INDICATION: Each unit is equipped with a "max-hand" that is moved upscale by the temperature indication pointer.

Mountain Controls









Portable Ventilators
Fans & Blowers
Welding Fume Exhausters
Ducts







POWERS
PROCESS CONTROLS
Quality...Our Commitment

Control Valves – Globe Type Temperature Regulators Self-Contained Temperature Controllers









Pressure Gauges Thermometers Needle Valves and Diaphragm Seals







Precision Air Regulators Air, Gas, Steam & Water Regulators Vacuum and Backpressure Regulators I/P and E/P Transducers





Electric Actuators Modulating Controllers Spring Return – SURE Mounting to your valves.







Solenoid Valves Water – Air – Hot Water – Steam Pilot Valves





Process Controllers Multi-Loop Process Indicators with Switches





Ball Valves and Actuators Spring Return Electric Actuators Resilient Seated Butterfly Valves High Performance Butterfly Valves







Ball Valves – 3-piece Pneumatic Actuators Electric Actuators Specialty Valves





Valve Actuator Mounting We stock electric actuators and can provide the mounting and testing to the valve of your choice



Salt Lake City, UT 84109 Phone: 801-487-8795

Seattle, WA 98125 Phone: 206-316-2330

www.mountaincontrols.com

info@mountaincontrols.com